

### PRODUCT SPECIFICATION

In-wall recessed bottle filling station for use with EDFPBM SwirlFlo® fountains with high-efficiency ECH8GRN chilling unit. LZWSSGRN(M)8PK shall deliver 8 GPH of 50° F drinking water at 90° F ambient and 80° F inlet water. Units shall be stainless steel construction with plastic ABS alcove. Sensor-activation with an auto 20-second shut-off timer. Shall include Green Ticker™ displaying count of plastic bottles saved from waste. Bottle filler shall provide 1.1 gpm flow rate with laminar flow to minimize splashing. Shall include the WaterSentry® Plus 3000-gallon capacity filter, certified to NSF/ANSI 42 and 53, with visual monitor to indicate when replacement is necessary. Shall include integrated silver ion anti-microbial protection in key areas. Unit shall meet ADA guidelines. Unit shall be lead-free design which is certified to NSF/ANSI 61 and 372 and meets Federal and State low-lead requirements. Unit shall be certified to UL399 and CAN/CSA 22.2 No. 120.

### STANDARD FEATURES

- High-efficiency ECH8GRN chilling unit
- Special panel height designed to pair with non-refrigerated EDFPBM SwirlFlo® models
- No-touch, sensor-activated operation
- Auto 20-second shut-off
- WaterSentry® Plus 3000-gallon capacity Filtration System, certified to NSF/ANSI 42 & 53 (Lead, Class 1 Particulate, Chlorine, Taste & Odor)
- Integrated Silver Ion Anti-microbial Protection in key areas
- Quick Fill Rate: 1.1 gpm
- Laminar Flow provides minimal splash
- Real Drain System eliminates standing water
- Visual User Interface display includes:
  - Innovative Green Ticker™ counts bottles saved from waste.
  - LED Visual Filter Monitor shows when replacement is necessary

### COOLING SYSTEM

- High-efficiency compressor: hermetically-sealed, reciprocating type, single phase. Sealed-in lifetime lubrication.
- Condenser: Fan cooled. Fan motor is permanently lubricated.
- Cooling Unit: Combination tube-tank type. Continuous copper tubing with stainless steel tank. Fully insulated with EPS foam which meets UL requirements for self-extinguishing material.
- Refrigerant Control: Refrigerant R134a is controlled by accurately calibrated capillary tube.
- Temperature Control: Enclosed adjustable thermostat is factory preset. Requires no adjustment other than for altitude requirements, Easily accessible by removing lower grille panel.

### CAPACITIES CHART

Model*	Voltage / Hertz	Chilling** Capacity	F.L. Amps	Rated Watts	Approx. Ship Wt.
LZWSSGRN(M)8PK	115V / 60Hz	8 GPH	3.8	260	76

\*Models with "M" include MFWS100 mounting frame, When mounting is pre-ordered, use models without "M".

\*\*Based on 80° F inlet water & 90° F ambient air temp for 50° F chilled drinking water.

### RATED FOR INDOOR USE ONLY



Model  
LZWSSGRN(M)8PK

### CONSTRUCTION

- Stainless steel bottle filler construction with ABS plastic alcove
- Includes stainless steel louvered ventilating grille
- Furnished with MFWS100 wall mounting box constructed of galvanized steel. Mounting can be ordered separately for pre-install.

**Replacement Filters:** Available as Singles and Multi-packs. Order part numbers:

- 51300C (single)
- 51300C\_3PK (three)
- 51300C\_12PK (twelve)
- 51300C\_24PK (twenty-four)
- 51300C\_48PK (forty-eight)

**Warranty:** 5 year limited warranty on the unit's refrigeration system. Electrical components and water system are warranted for 12 months from date of installation or 18 months from factory shipment, whichever date falls first.

### CERTIFICATIONS / STANDARDS

- ADA Compliant
- UL399 and CAN/CSA 22.2 No. 120 Certified (Only 115V models are certified)
- ANSI/NSF 61 and 372 Certified
- ANSI/NSF 42 and 53 Certified (Filter only)
- GreenSpec® Listed






This specification describes an Elkay product with design, quality and functional benefits to the user. When making a comparison of other producer's offerings, be certain these features are not overlooked.

**EZH20<sup>®</sup> In-Wall Bottle Filling Station (for use with SwirFlo<sup>®</sup> EDFPBM) with High-efficiency ECH8GRN Chiller Filtered Model LZWSGRN(M)8PK**

**ELKAY<sup>®</sup>**  
**ROUGH-IN**

Job Name: \_\_\_\_\_  
 Date: \_\_\_\_\_ Qty: \_\_\_\_\_  
 Contact Info (Name, Phone, Email): \_\_\_\_\_  
 \_\_\_\_\_  
 Approval: \_\_\_\_\_

**IMPORTANT:**  
**DOUBLE STUD OR 3 INCHES (76 mm)**  
**BETWEEN MOUNTING FRAMES**  
**IF PLACED NEXT TO ANOTHER**  
**BOTTLE FILLER, FOUNTAIN OR WALL**



NOTE - NON-REFRIGERATED MODELS (WITHOUT CHILLER) DO NOT INCLUDE LOUVERS

