

ELKAY®

SPECIFICATIONS

No Lead Two-Level SwirlFlo® Wall Mount, Barrier-Free Refrigerated Fountain with EZH2O® Bottle Filling Station Model EZWS-ERPBM28K

PRODUCT SPECIFICATION

Architectural fountains with integral bottle filling station. EZWS-LRPBM28K shall deliver 8 GPH of 50°F drinking water at 90°F ambient and 80°F inlet water. Units shall be stainless steel construction with plastic ABS alcove. Sensor-activation with an auto 20-second shut-off timer. Shall include Green Ticker™ displaying count of plastic bottles saved from waste. Bottle filler shall provide 1.1 gpm flow rate with laminar flow to minimize splashing. Shall include integrated silver ion anti-microbial protection in key areas. Unit shall meet ADA guidelines. Unit shall be lead-free design which is certified to NSF/ANSI 61 and 372 and meets Federal and State low-lead requirements. Unit shall be certified to UL399 and CAN/CSA 22.2 No. 120.

Rated for Indoor Use Only

FOUNTAINS GENERAL

Fully exposed two-level fountain basins are #18 gauge, 300 series stainless steel polished to a lustrous satin finish with high shine outer edge. #16 gauge, 300 series tubular stainless steel support arms incorporate unique recess to be integrated with basin. One fountain positioned lower on the right for wheel-chair use. The other positioned on the left at standing height.

Fountains have contoured basin that minimizes splashing. Flexi-Guard® Safety bubblers are keyed in location to prevent rotation. Fully functional, vandal-resistant front push button. Flow regulator provides constant stream from 20 to 105 psi water pressure.

BOTTLE FILLER STANDARD FEATURES

- No-touch, sensor-activated bottle filler with auto 20-second shut-off.
- Front Pushbutton activation on fountains.
- Integrated Silver Ion Anti-microbial Protection in key areas.
- Quick Fill Rate: 1.1 gpm.
- Laminar Flow provides minimal splash.
- Real Drain System eliminates standing water.
- Visual User Interface display includes:
 - Innovative Green Ticker™ counts bottles saved from waste.
- Includes lower panel for easy access and servicing.

OPTIONAL FEATURES (Additional Cost)

- -For front access to bottle filler electricals, use access panel (Item #ACCESS12X38-5)



Shown with one optional access panel installed



Model
EZWS-ERPBM28K

COOLING SYSTEM

- Compressor: Hermetically-sealed, reciprocating type, single phase. Sealed-in lifetime lubrication.
- Condenser: Fan cooled. Fan motor is permanently lubricated.
- Cooling Unit: Combination tube-tank type. Continuous copper tubing with stainless steel tank. Fully insulated with EPS foam which meets UL requirements for self-extinguishing material.
- Refrigerant control: Refrigerant R134a is controlled by accurately calibrated capillary tube.
- Temperature Control: Enclosed adjustable thermostat is factory preset. Requires no adjustment other than for altitude requirements, easily accessible by removing lower grille panel.

CAPACITIES CHART

| Model | Voltage / Hertz | Chilling Capacity | F.L. Amps | Rated Watts | Approx. Ship Wt. |
|---------------|-----------------|-------------------|-----------|-------------|------------------|
| EZWS-ERPBM28K | 115V / 60Hz | 8 GPH | 5.0 | 370 | 174 |

CONSTRUCTION

EZWS-ERPBM28K two-level fountain furnished complete with Flexi-Guard® fully assembled with front push button, flow regulator (120 to 105 psi), stainless steel back panel. No traps are furnished.

- Stainless Steel bottle filler construction with ABS plastic alcove.
- Includes stainless steel lower panel.
- Furnished with wall mounting frame constructed of galvanized steel. Mounting can be ordered separately for pre-install.

Warranty: 5 year limited warranty on the unit's refrigeration system. Electrical components and water system are warranted for 12 months from date of installation or 18 months from factory shipment, whichever date falls first.

CERTIFICATIONS / STANDARDS

- ADA Compliant
- UL399 and CAN/CSA 22.2 No. 120 Certified
- ANSI/NSF 61 and 372 Certified
- GreenSpec® Listed



C USA

In Keeping with our policy of continuing product improvement, Elkay reserves the right to change specification without notice. Please visit elkayusa.com

2222 Camden Court
OakBrook, IL 60523
630-572-3192
elkayusa.com

2013 Elkay
SPEC00047 (Rev 08/2013)

No Lead Two-Level SwirlFlo®

Wall Mount, Barrier-Free Refrigerated Fountain with EZH2O® Bottle Filling Station

Model EZWS-ERPBM28K

ELKAY®

ROUGH-IN DIMENSIONS

INSTALLER NOTE:

THIS DRINKING FOUNTAIN IS FURNISHED WITH A BUBBLER AND VALVE INCLUDING ALL CONNECTING FITTINGS WHICH ARE MANUFACTURED OF COMPLETELY LEAD FREE MATERIAL. SHUTOFF VALVE (NOT FURNISHED) TO ACCEPT 3/8" O.D. UNPLATED COPPER TUBE.

WALL OPENING

IMPORTANT: It is necessary to create a wall opening 37 1/2" W x 51-15/16" H and 4-1/2" above the floor line.

ELECTRICAL DATA

Junction box for a (3) wire 10 AMP branch circuit. Standard 120 Volt, 60 Hz, single phase.

Electrical outlet, three (3) conductor grounded. Locate within safe reach of power cord.

MOUNTING INSTRUCTIONS

Refer to rough-in for location of plumbing and electrical sources. The support frame is to be installed first. Hang upper panel to hanger on frame. Fountains are to be attached to panel and wall frame. Water service lines, waste lines and electrical are assembled as required. Perform a final check for leaks and correct functions of fountains and chiller. (For details see the installation instructions.)

Installation requires trap to be installed in wall. Trap and service stop not included.

Job Name: _____

Date: _____ Qty. _____

Contact Info (Name, Phone, Email): _____

Approval: _____

OPERATION OF QUICK CONNECT FITTINGS

